

Model Number 3741E1225G	DC RESPONSE ACCELEROMETER			Revision: B ECN #: 44052
Performance	ENGLISH	SI		OPTIONAL VERSIONS
Sensitivity(± 3 %)	160 mV/g	16.3 mV/(m/s ²)	[6]	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Measurement Range	± 25 g pk	± 245.3 m/s ² pk		
Frequency Range(± 3 dB)	0 to 750 Hz	0 to 750 Hz	[7]	
Frequency Range(± 3 dB)	0 to 1500 Hz	0 to 1500 Hz	[2]	
Phase Response(100 Hz)	<10 °	<10 °		
Broadband Resolution(0.5 to 100 Hz)	.6 mg rms	.0059 m/s ² rms	[2]	
Non-Linearity	≤ 1 %	≤ 1 %	[8]	
Transverse Sensitivity	≤ 5 %	≤ 5 %		
Environmental				
Overload Limit(Shock)	± 5000 g pk	± 49,050 m/s ² pk		
Temperature Range(Operating)	-65 to 250 °F	-54.0 to 121 °C		
Temperature Range(Storage)	-65 to 250 °F	-54.0 to 121 °C		
Temperature Coefficient of Sensitivity	± 3.0 %	± 3.0 %	[4]	
Zero g Offset Temperature Coefficient	± 2.0 % FSO	± 2.0 % FSO	[5][4]	
Base Strain Sensitivity(Measured at 250 µε)	.001 g	.01 m/s ²	[2]	
Electrical				
Excitation Voltage	6 to 30 VDC	6 to 30 VDC		
Current Consumption	≤ 10 mA	≤ 10 mA		
Output Impedance	≤ 120 Ohm	≤ 120 Ohm		
Offset Voltage(0 g)	± 160 mVDC	± 160 mVDC	[1]	
Common Mode Voltage(± 0.1 VDC)	+2.5 VDC	+2.5 VDC		
Spectral Noise(1 to 100 Hz)	100 µg/√Hz	981 (µm/sec ²)/√Hz	[2]	
Electrical Isolation(Case)	>10 ⁸ Ohm	>10 ⁸ Ohm	[3]	
Physical				
Housing Material	Anodized Aluminum	Anodized Aluminum		
Sealing	Epoxy	Epoxy		
Size (Height x Length x Width)	0.30 in x 1.00 in x .85 in	7.5 mm x 25.4 mm x 21.6 mm		
Weight(without cable)	.35 oz	9.92 gm	[2]	
Electrical Connector	Integral Cable	Integral Cable		
Electrical Connection Position	Side	Side		
Cable Termination	Pigtail Ends	Pigtail Ends		
Cable Type	010 4-cond Shielded	010 4-cond Shielded		
Cable Length	10 ft	10 ft		
Mounting	Through Holes (2)	Through Holes (2)		
				NOTES:
				[1]Offset tolerance is based on manufacturers supplied cable length.
				[2]Typical.
				[3]Case and shield to mounting surface or cable leads.
				[4]-65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)
				[5]FSO = Full Scale Output over the Measurement Range (8VDC).
				[6]Measured at 100 Hz, 1 grms.
				[7]Minimum, verified with Calibration data.
				[8]Least-squares, straight line method, % FSO.
				[9]See PCB Declaration of Conformance PS027 for details.
				SUPPLIED ACCESSORIES:
				Model 081A103 Mounting screw (2)
				Model ACS-145 Phase and Amplitude Calibration from 2 Hz to ±3 dB of frequency range (1)
				Model M081A103 Mounting screw and washer, M3 x 0.5 thread (2)
				OPTIONAL ACCESSORIES:
				Model 080A208 Triaxial mounting block
Entered: AP		Engineer: JJD		Sales: RM
Date: 4/9/2015		Date: 4/9/2015		Date: 4/9/2015
		Approved: NJF		Spec Number:
				60169
				Phone: 716-684-0001
				Fax: 716-684-0987
				E-Mail: info@pcb.com



All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.



3425 Walden Avenue, Depew, NY 14043



Represented in India by
Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com
#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029