



Model Number HT378B02	ICP MICROPHONE SYSTEM			Revision: E ECN #: 45005
Performance	ENGLISH	SI		OPTIONAL VERSIONS
Nominal Microphone Diameter	1/2"	1/2"		Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Frequency Response Characteristic(at 0° incidence)	Free-Field	Free-Field		
Sensitivity	50 mV/Pa	50 mV/Pa	[4]	
Sensitivity(± 1.5 dB)	-26 dB re 1 V/Pa	-26 dB re 1 V/Pa	[4]	
Frequency Range(± 1 dB)	6 to 10,000 Hz	6 to 10,000 Hz		
Frequency Range(± 2 dB)	3.5 to 20,000 Hz	3.5 to 20,000 Hz		
Lower Limiting Frequency(-3 dB)	1.0 to 2.75 Hz	1.0 to 2.75 Hz		
Inherent Noise	16 dB(A) re 20 µPa	16 dB(A) re 20 µPa	[3]	
Dynamic Range(3% Distortion Limit)	138.5 dB re 20 µPa	138.5 dB re 20 µPa	[3]	
TEDS Compliant	Yes	Yes	[5]	
Environmental				NOTES: [1] Prepolarized [2] Limited to 120°C if ICP current > 4 mA [3] Typical. [4] re 250 Hz [5] TEDS Capable Digital Communication, compliant with IEEE 1451.4 [6] Venting through Preamp. [7] See PCB Declaration of Conformance PS065 for details.
Temperature Range(Operating)	-40 to +257 °F	-40 to +125 °C	[2]	
Temperature Coefficient of Sensitivity(+14 to +158°F (-10 to +70°C))	0.005 dB/°F	0.009 dB/°C	[3][4]	
Static Pressure Coefficient	-0.013 dB/kPa	-0.013 dB/kPa	[3][4]	
Humidity Coefficient of Sensitivity(0 to 100%, non-condensing)	± 0.001 dB/%RH	± 0.001 dB/%RH	[4]	
Influence of Axial Vibration(0.1g (1 m/s ²))	63 dB re 20 µPa	63 dB re 20 µPa	[3]	
Electrical				
Polarization Voltage	0 V	0 V	[1]	
Excitation Voltage	20 to 32 VDC	20 to 32 VDC		
Constant Current Excitation	2 to 10 mA	2 to 10 mA		
Output Bias Voltage	10 to 14 VDC	10 to 14 VDC		
Maximum Output Voltage	± 7 Vpk	± 7 Vpk		
Output Impedance	<55 Ohm	<55 Ohm		
Physical				SUPPLIED ACCESSORIES: Model ACS-63 Calibration (with TEDS) of Precision Condenser Microphones and Preamplifiers together (mated pair). (1)
Housing Material	Stainless Alloy	Stainless Alloy		
Venting	Rear	Rear	[6]	
Electrical Connector	BNC Jack	BNC Jack		
Mounting Thread(Grid)	0.5 - 60 UNS	0.5 - 60 UNS		
Size (Diameter x Height)(with grid)	.52 in x 3.88 in	13.2 mm x 98.6 mm		
Size (Diameter x Height)(without grid)	.50 in x 3.84 in	12.7 mm x 97.5 mm		
Weight	1.74 oz	49.2 gm	[3]	
				
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.				
		Entered: LK		Engineer: MT
		Date: 10/13/2016		Date: 10/13/2016
		Date: 10/13/2016		Date: 10/13/2016
		Date: 10/13/2016		Spec Number: 57825
				
				Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com
				3425 Walden Avenue, Depew, NY 14043



Represented in India by

Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029