




Model Number 649A03	BEARING FAULT DETECTOR PLUS			Revision: F ECN #: 45941
Performance	ENGLISH	SI		OPTIONAL VERSIONS
Output(Loop power)	4-20 mA	4-20 mA		Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Sampling Time	1 sec	1 sec		CS - Canadian Standards Association Approved Intrinsically Safe
Measurement Range(HPF 250 Hz)	0-2 to 0-50 g pk	0-2 to 0-50 g pk	[1][2]	M - Metric Mount
Measurement Range(HPF 2500 Hz)	0-2 to 0-50 RMS	0-2 to 0-50 RMS	[1][2]	Supplied Accessory : Model M081A61 Mounting Stud 1/4-28 to M6 X 1 (1)
Compensated Peak(HPF 250 Hz)	1 to 16	1 to 16	[1]	
Crest Factor(HPF 250 Hz)	1 to 16	1 to 16	[1]	
Crest Factor Plus(HPF 250 Hz)	1 to 16	1 to 16	[1]	
Bearing Diameter	1.57 to 19.69 in	40 to 500 mm		
Bearing Rotation Speed	600 to 4800 RPM	10 to 80 Hz		
Linearity(Loop powered)	10 %	10 %		
Environmental				
Temperature Range	-40 to 212 °F	-40 to 100 °C		
Storage Temperature Range	-40 to 257 °F	-40 to 125 °C		
Electrical				NOTES:
Excitation Voltage	15 to 30 VDC	15 to 30 VDC		[1] Customer programmable parameters
Load Resistance	50(Vs-15) Ohm	50(Vs-15) Ohm		[2] With 0.1g Step
Electrical Isolation	>10^8 Ohm	>10^8 Ohm		[3] Typical.
Physical				[4] See PCB Declaration of Conformance PS124 for details.
Size (Height x Hex)	2.60 in x 1.25 in	66 mm x 32 mm		
Weight	5.7 oz	162 gm	[3]	
Mounting Thread	1/4 - 28 UNF	1/4 - 28 UNF		
Mounting Torque	3 to 5 ft-lb	4 to 7 Nm		
Sensing Element	Piezoelectric Accelerometer	Piezoelectric Accelerometer		
Housing Material	Stainless Steel	Stainless Steel		
Sealing	Welded Hermetic	Welded Hermetic		
Electrical Connector	2-Pin MIL-C-5015	2-Pin MIL-C-5015		
Electrical Connection Position	Top	Top		
Electrical Connections(Pin A)	4-20 mA Pos (+)	4-20 mA Pos (+)		
Electrical Connections(Pin B)	4-20 mA Neg (-)	4-20 mA Neg (-)		
Overload Limit (Shock)	5000 g pk	49,050 m/s ² pk		
 [4]				SUPPLIED ACCESSORIES:
				Model 081A41 Mounting stud 1/4-28 socket head set screw brass tip stainless steel 5/8" long (1)
<i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>				Entered: LK Engineer: NJF Sales: MC Approved: NJF Spec Number:
ICP® is a registered trademark of PCB Group, Inc.				Date: 9/12/2016 Date: 9/12/2016 Date: 9/12/2016 Date: 9/12/2016 45609
				 IMI SENSORS A PCB PIEZOTRONICS DIV. 3425 Walden Avenue, Depew, NY 14043
				Phone: 800-959-4464 Fax: 716-684-3823 E-Mail: imi@pcb.com



Represented in India by

Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029