

	<u>ENGLISH</u>	<u>SI</u>	
<b>Performance</b>			
Sensitivity(± 50 %)(at 10 VDC excitation)	0.20 mV/g	0.020 mV/(m/s <sup>2</sup> )	[2]
Measurement Range	± 2000 g pk	± 19,620 m/s <sup>2</sup> pk	
Frequency Range(± 5 %)	0 to 5000 Hz	0 to 5000 Hz	
Resonant Frequency	>20 kHz	>20 kHz	
Damping Ratio(± 0.3)	0.7 critical	0.7 critical	[1]
Non-Linearity	± 1 %	± 1 %	[7]
Transverse Sensitivity	≤ 2 %	≤ 2 %	
<b>Environmental</b>			
Overload Limit(Shock)	± 10,000 g pk	± 98,100 m/s <sup>2</sup> pk	[5][4]
Overload Limit(Mechanical Stops)	≥ 2200 g pk	≥ 21,582 m/s <sup>2</sup> pk	
Temperature Range(Operating)	0 to 150 °F	-18 to 66 °C	
Temperature Range(Storage)	-65 to 250 °F	-54 to 121 °C	
Temperature Coefficient of Sensitivity	-0.10 %/°F	-0.18 %/°C	[1]
Zero g Offset Temperature Shift	± 20 mV	± 20 mV	[6]
Base Strain Sensitivity	0.01 g/με	0.1 (m/s <sup>2</sup> )/με	[1]
<b>Electrical</b>			
Excitation Voltage(Maximum)	15 VDC	15 VDC	
Current Consumption	<10 mA	<10 mA	[1]
Input Resistance(± 1250 Ohm)	2750 Ohm	2750 Ohm	[2]
Output Resistance(± 1250 Ohm)	2750 Ohm	2750 Ohm	[2]
Offset Voltage	± 50 mVDC	± 50 mVDC	[2]
Settling Time	0.01 sec	0.01 sec	[3]
Electrical Isolation(Case)	≥ 10 <sup>8</sup> Ohm	≥ 10 <sup>8</sup> Ohm	[4]
<b>Physical</b>			
Sensing Element	Piezoresistive MEMS	Piezoresistive MEMS	
Sensing Geometry	Full Active	Full Active	
Housing Material	Anodized Aluminum	Anodized Aluminum	
Sealing	Epoxy	Epoxy	
Size (Height x Length x Width)	0.200 in x 0.470 in x 0.400 in	5.08 mm x 11.94 mm x 10.16 mm	[1]
Weight(without cable)	0.035 oz	1 gm	
Electrical Connector	Integral Cable	Integral Cable	
Electrical Connection Position	Side	Side	
Cable Type	036 4-cond silicone jacket	036 4-cond silicone jacket	
Cable Termination	Pigtail Ends	Pigtail Ends	
Cable Length	30 ft	9.14 m	
Mounting	Through Holes (2)	Through Holes (2)	

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**

[1] Typical.  
 [2] Verified with test data provided on supplied calibration certificate.  
 [3] Settling Time is the maximum time after power-up for the Offset Voltage to be within +/-2% of Measurement Range output of the final offset value. Mounting surface must be at thermal equilibrium.  
 [4] Individually tested to ensure compliance with specified value.  
 [5] Half-sine pulse duration, ≥ 200 μsec.  
 [6] -65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)  
 [7] % deviation per 1000g

**SUPPLIED ACCESSORIES:**

Model 039A30 Allen wrench, 0.050 hex (1)  
 Model 080A191 Skt hd cap screw, QTY 2,0-80x3/16" with washer (1)  
 Model ACS-29 Calibration of Piezoresistive Accelerometers

Entered: LK	Engineer: LAB	Sales: JC	Approved: NJF	Spec Number:
Date: 3/21/2017	Date: 3/21/2017	Date: 3/21/2017	Date: 3/21/2017	<b>51410</b>

*All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.*

ICP® is a registered trademark of PCB Group, Inc.



3425 Walden Avenue, Depew, NY 14043

**Phone: 716-684-0001**  
**Fax: 716-684-0987**  
**E-Mail: info@pcb.com**