

	ENGLISH	SI	
Performance			
Sensitivity (± 15 %) (z axis)	15 pC/lb	3.37 pC/N	[2]
Sensitivity (± 15 %) (x or y axis)	32 pC/lb	7.19 pC/N	[2]
Measurement Range (z axis)	1000 lb	4.45 kN	
Measurement Range (x or y axis)	500 lb	2.22 kN	
Maximum Force (z axis)	1320 lb	5.87 kN	
Maximum Force (x or y axis)	660 lb	2.94 kN	
Maximum Moment (z axis)	14 ft-lb	18.98 N-m	
Maximum Moment (x or y axis)	13 ft-lb	17.63 N-m	
Upper Frequency Limit	90 kHz	90 kHz	
Non-Linearity	≤ 1 % FS	≤ 1 % FS	[3]
Cross Talk (between x and y axis)	± 3 %	± 3 %	
Cross Talk (between (x or y axis) and z axis)	± 5 %	± 5 %	
Environmental			
Temperature Range	-100 to +350 °F	-73 to +177 °C	
Electrical			
Capacitance (all channels)	18 pF	18 pF	[1]
Insulation Resistance (all channels)	≥ 10 ¹² ohm	≥ 10 ¹² ohm	
Output Polarity (in direction of markings)	Negative	Negative	
Physical			
Preload	≤ 5000 lb	≤ 22.25 kN	[4]
Stiffness (z axis)	10 lb/μin	1.75 kN/μm	[1]
Stiffness (x or y axis)	4 lb/μin	0.7 kN/μm	[1]
Size (Height x Length x Width x Bolt Diameter x ID x Sensing Surface)	0.390 in x 0.950 in x 0.950 in x .313 in x 0.319 in x 0.680 in	9.90 mm x 24.1 mm x 24.1 mm x 8 mm x 8.10 mm x 17.27 mm	
Weight	0.868 oz	24.59 gm	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Hermetic	Hermetic	
Electrical Connector (Quantity, 3)	10-32 Coaxial Jack	10-32 Coaxial Jack	
Electrical Connection Position	Side	Side	

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

M - Metric Mount
Supplied Accessory : Model M081A70 Mounting Stud (1) replaces Model 081A70

W - Water Resistant Cable
Electrical Connection Position Side Side

NOTES:

[1] Typical.
 [2] Sensitivites are for listed preload. Sensitivites may vary ±5% depending on preload used.
 [3] Zero-based, least-squares, straight line method.
 [4] Preload should be at least 10 times the X and Y operating range used.

SUPPLIED ACCESSORIES:

Model 081A70 Mounting Stud (1)
 Model 082B02 Anti-Friction Washer (1)
 Model 083A10 Pilot Bushing (1)

Entered: <i>BLS</i>	Engineer: <i>mjk</i>	Sales: <i>Jm</i>	Approved: <i>Dmb</i>	Spec Number:
Date: <i>11/7/05</i>	Date: <i>11-9-05</i>	Date: <i>11/10/05</i>	Date: <i>11/10/05</i>	6232



PCB PIEZOTRONICS
FORCE / TORQUE DIVISION
3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
 Fax: 716-684-8877
 E-Mail: force@pcb.com

*All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.*

ICP® is a registered trademark of PCB Group, Inc.


Represented in India by
Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com
 #4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029