



Model Number <b>3741E1250G</b>		<b>DC RESPONSE ACCELEROMETER</b>		Revision: B ECN #: 44052
<b>Performance</b>	<b>ENGLISH</b>	<b>SI</b>		<b>OPTIONAL VERSIONS</b>
Sensitivity(± 3 %)	80 mV/g	8.15 mV/(m/s <sup>2</sup> )	[6]	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Measurement Range	± 50 g pk	± 490.5 m/s <sup>2</sup> pk		
Frequency Range(± 3 dB)	0 to 1000 Hz	0 to 1000 Hz	[7]	
Frequency Range(± 3 dB)	0 to 2000 Hz	0 to 2000 Hz	[2]	
Phase Response(100 Hz)	<10 °	<10 °		
Broadband Resolution(0.5 to 100 Hz)	1.0 mg rms	0.010 m/s <sup>2</sup> rms	[2]	
Non-Linearity	≤ 1 %	≤ 1 %	[8]	
Transverse Sensitivity	≤ 5 %	≤ 5 %		
<b>Environmental</b>				
Overload Limit(Shock)	± 5000 g pk	± 49,050 m/s <sup>2</sup> pk		
Temperature Range(Operating)	-65 to 250 °F	-54 to 121 °C		
Temperature Range(Storage)	-65 to 250 °F	-54.0 to 121 °C		
Temperature Coefficient of Sensitivity	± 3.0 %	± 3.0 %	[4]	
Zero g Offset Temperature Coefficient	± 2.0 % FSO	± 2.0 % FSO	[5][4]	
Base Strain Sensitivity(Measured at 250 µε)	.001 g/µε	.010 (m/s <sup>2</sup> )/µε	[2]	
<b>Electrical</b>				<b>NOTES:</b>
Excitation Voltage	6 to 30 VDC	6 to 30 VDC		[1]Offset tolerance is based on manufacturers supplied cable length.
Current Consumption	≤ 10 mA	≤ 10 mA		[2]Typical.
Output Impedance	≤ 120 Ohm	≤ 120 Ohm		[3]Case and shield to mounting surface or cable leads.
Offset Voltage(0 g)	± 160 mVDC	± 160 mVDC	[1]	[4]-65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)
Common Mode Voltage(± 0.1 VDC)	+2.5 VDC	+2.5 VDC		[5]FSO = Full Scale Output over the Measurement Range (8VDC).
Spectral Noise(1 to 100 Hz)	200 µg/√Hz	1962 (µm/sec <sup>2</sup> )/√Hz	[2]	[6]Measured at 100 Hz, 1 grms.
Electrical Isolation(Case)	>10 <sup>8</sup> Ohm	>10 <sup>8</sup> Ohm	[3]	[7]Minimum, verified with Calibration data.
<b>Physical</b>				[8]Least-squares, straight line method, % FSO.
Housing Material	Anodized Aluminum	Anodized Aluminum		[9]See PCB Declaration of Conformance PS027 for details.
Sealing	Epoxy	Epoxy		<b>SUPPLIED ACCESSORIES:</b>
Size (Height x Length x Width)	0.30 in x 1.00 in x .85 in	7.5 mm x 25.4 mm x 21.6 mm		Model 081A103 Mounting screw (2)
Weight(without cable)	0.35 oz	9.92 gm	[2]	Model ACS-145 Phase and Amplitude Calibration from 2 Hz to ±3 dB of frequency range (1)
Electrical Connector	Integral Cable	Integral Cable		Model M081A103 Mounting screw and washer, M3 x 0.5 thread (2)
Electrical Connection Position	Side	Side		<b>OPTIONAL ACCESSORIES:</b>
Cable Termination	Pigtail Ends	Pigtail Ends		Model 080A208 Triaxial mounting block
Cable Type	010 4-cond Shielded	010 4-cond Shielded		
Cable Length	10 ft	10 ft		
Mounting	Through Holes (2)	Through Holes (2)		
				Entered: AP    Engineer: JJD    Sales: RM    Approved: NJF    Spec Number:
				Date: 4/9/2015    Date: 4/9/2015    Date: 4/9/2015    Date: 4/9/2015 <b>60428</b>
 <p>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</p>				 <p><b>Phone: 716-684-0001</b> <b>Fax: 716-684-0987</b> <b>E-Mail: info@pcb.com</b></p> <p>3425 Walden Avenue, Depew, NY 14043</p>



Represented in India by

**Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com**

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029