

Model Number 3124-02A	ROTARY TORQUE TRANSFORMER, SHAFT-SHAFT		Revision: NR ECN #:																																																									
Performance Measurement Range(Full Scale Capacity) Sensitivity(output at rated capacity) Non-Linearity Hysteresis Non-Repeatability	<table border="0"> <tr> <td></td> <td style="text-align: center;">ENGLISH</td> <td style="text-align: center;">SI</td> <td></td> </tr> <tr> <td></td> <td>1000 in-lb</td> <td>113 N-m</td> <td></td> </tr> <tr> <td></td> <td>2.0 mV/V</td> <td>2.0 mV/V</td> <td>[4]</td> </tr> <tr> <td></td> <td>≤ 0.1 % FS</td> <td>≤ 0.1 %</td> <td>[2]</td> </tr> <tr> <td></td> <td></td> <td>FS</td> <td></td> </tr> <tr> <td></td> <td>≤ 0.1 % FS</td> <td>≤ 0.1 %</td> <td>[2]</td> </tr> <tr> <td></td> <td></td> <td>FS</td> <td></td> </tr> <tr> <td></td> <td>≤ 0.05 %</td> <td>≤ 0.05 %</td> <td>[2]</td> </tr> <tr> <td></td> <td>FS</td> <td>FS</td> <td></td> </tr> </table>		ENGLISH	SI			1000 in-lb	113 N-m			2.0 mV/V	2.0 mV/V	[4]		≤ 0.1 % FS	≤ 0.1 %	[2]			FS			≤ 0.1 % FS	≤ 0.1 %	[2]			FS			≤ 0.05 %	≤ 0.05 %	[2]		FS	FS		<table border="0"> <tr> <td colspan="4" style="text-align: center;">OPTIONAL VERSIONS</td> </tr> <tr> <td colspan="4">Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.</td> </tr> </table>			OPTIONAL VERSIONS				Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.															
	ENGLISH	SI																																																										
	1000 in-lb	113 N-m																																																										
	2.0 mV/V	2.0 mV/V	[4]																																																									
	≤ 0.1 % FS	≤ 0.1 %	[2]																																																									
		FS																																																										
	≤ 0.1 % FS	≤ 0.1 %	[2]																																																									
		FS																																																										
	≤ 0.05 %	≤ 0.05 %	[2]																																																									
	FS	FS																																																										
OPTIONAL VERSIONS																																																												
Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.																																																												
Environmental Overload Limit Temperature Range(Operating) Temperature Range(Compensated) Temperature Effect on Output(Maximum)	<table border="0"> <tr> <td></td> <td>2000 in-lb</td> <td>226 N-m</td> <td></td> </tr> <tr> <td></td> <td>0 to 200 °F</td> <td>-18 to 93 °C</td> <td></td> </tr> <tr> <td></td> <td>70 to 150 °F</td> <td>21 to 66 °C</td> <td></td> </tr> <tr> <td></td> <td>± 0.002 % Reading/°F</td> <td>± 0.0018 % Reading/°C</td> <td>[3]</td> </tr> </table>		2000 in-lb	226 N-m			0 to 200 °F	-18 to 93 °C			70 to 150 °F	21 to 66 °C			± 0.002 % Reading/°F	± 0.0018 % Reading/°C	[3]	<table border="0"> <tr> <td colspan="4">NOTES:</td> </tr> <tr> <td>[1]</td> <td colspan="3">Recommended 10 VAC RMS.</td> </tr> <tr> <td>[2]</td> <td colspan="3">FS - Full Scale.</td> </tr> <tr> <td>[3]</td> <td colspan="3">Over compensated operating temperature range.</td> </tr> <tr> <td>[4]</td> <td colspan="3">Nominal.</td> </tr> <tr> <td>[5]</td> <td colspan="3">See drawing 44773 for complete dimensions.</td> </tr> </table>			NOTES:				[1]	Recommended 10 VAC RMS.			[2]	FS - Full Scale.			[3]	Over compensated operating temperature range.			[4]	Nominal.			[5]	See drawing 44773 for complete dimensions.																		
	2000 in-lb	226 N-m																																																										
	0 to 200 °F	-18 to 93 °C																																																										
	70 to 150 °F	21 to 66 °C																																																										
	± 0.002 % Reading/°F	± 0.0018 % Reading/°C	[3]																																																									
NOTES:																																																												
[1]	Recommended 10 VAC RMS.																																																											
[2]	FS - Full Scale.																																																											
[3]	Over compensated operating temperature range.																																																											
[4]	Nominal.																																																											
[5]	See drawing 44773 for complete dimensions.																																																											
Temperature Effect on Zero Balance(Maximum)	<table border="0"> <tr> <td></td> <td>± 0.002 % FS/°F</td> <td>± 0.0018 %FS/°C</td> <td>[3]</td> </tr> </table>		± 0.002 % FS/°F	± 0.0018 %FS/°C	[3]	<table border="0"> <tr> <td colspan="5">Electrical</td> </tr> <tr> <td></td> <td>350 ohm</td> <td>350 ohm</td> <td></td> <td></td> </tr> <tr> <td></td> <td>20 VDC or VAC rms</td> <td>20 VDC or VAC rms</td> <td>[1]</td> <td></td> </tr> <tr> <td></td> <td>50 mA</td> <td>50 mA</td> <td></td> <td></td> </tr> <tr> <td></td> <td>>5 Gohm</td> <td>>5 Gohm</td> <td></td> <td></td> </tr> <tr> <td></td> <td>≤ 2 % FS</td> <td>≤ 2 % FS</td> <td>[2]</td> <td></td> </tr> </table>			Electrical						350 ohm	350 ohm				20 VDC or VAC rms	20 VDC or VAC rms	[1]			50 mA	50 mA				>5 Gohm	>5 Gohm				≤ 2 % FS	≤ 2 % FS	[2]																							
	± 0.002 % FS/°F	± 0.0018 %FS/°C	[3]																																																									
Electrical																																																												
	350 ohm	350 ohm																																																										
	20 VDC or VAC rms	20 VDC or VAC rms	[1]																																																									
	50 mA	50 mA																																																										
	>5 Gohm	>5 Gohm																																																										
	≤ 2 % FS	≤ 2 % FS	[2]																																																									
Physical Size (Shaft Length x Housing Length x Housing Diameter x Shaft Diameter x Shaft Keyway)	<table border="0"> <tr> <td></td> <td>9.00 in x 4.58 in x 4.00 in x 1.00 in x 1/4 in</td> <td>228.6 mm x 116.3 mm x mm x 101.6 mm x 25.4 mm x 6.3 mm</td> <td>[5]</td> </tr> </table>		9.00 in x 4.58 in x 4.00 in x 1.00 in x 1/4 in	228.6 mm x 116.3 mm x mm x 101.6 mm x 25.4 mm x 6.3 mm	[5]	<table border="1"> <tr> <td>Entered: BLS</td> <td>Engineer: PTE</td> <td>Sales: JCC</td> <td>Approved: MB</td> <td>Spec Number:</td> </tr> <tr> <td>Date: 3-29-10</td> <td>Date: 3-29-10</td> <td>Date: 3-29-10</td> <td>Date: 3-29-10</td> <td>45887</td> </tr> </table>			Entered: BLS	Engineer: PTE	Sales: JCC	Approved: MB	Spec Number:	Date: 3-29-10	Date: 3-29-10	Date: 3-29-10	Date: 3-29-10	45887																																										
	9.00 in x 4.58 in x 4.00 in x 1.00 in x 1/4 in	228.6 mm x 116.3 mm x mm x 101.6 mm x 25.4 mm x 6.3 mm	[5]																																																									
Entered: BLS	Engineer: PTE	Sales: JCC	Approved: MB	Spec Number:																																																								
Date: 3-29-10	Date: 3-29-10	Date: 3-29-10	Date: 3-29-10	45887																																																								
Weight Mounting Sensing Element Housing Material Shaft Material Electrical Connector Electrical Connection Position Rotating Inertia Maximum Speed	<table border="0"> <tr> <td></td> <td>5.3 lb</td> <td>2.4 kg</td> <td></td> </tr> <tr> <td></td> <td>Keyed</td> <td>Keyed</td> <td></td> </tr> <tr> <td></td> <td>Shaft</td> <td>Shaft</td> <td></td> </tr> <tr> <td></td> <td>Strain</td> <td>Strain</td> <td></td> </tr> <tr> <td></td> <td>Gage</td> <td>Gage</td> <td></td> </tr> <tr> <td></td> <td>Aluminum</td> <td>Aluminum</td> <td></td> </tr> <tr> <td></td> <td>Alloy Steel</td> <td>Alloy Steel</td> <td></td> </tr> <tr> <td></td> <td>PT02H-10-6P</td> <td>PT02H-10-6P</td> <td></td> </tr> <tr> <td></td> <td>Top</td> <td>Top</td> <td></td> </tr> <tr> <td></td> <td>0.48 in-lb/sec²</td> <td>0.48 in-lb/sec²</td> <td></td> </tr> <tr> <td></td> <td>7900 RPM</td> <td>7900 RPM</td> <td></td> </tr> </table>		5.3 lb	2.4 kg			Keyed	Keyed			Shaft	Shaft			Strain	Strain			Gage	Gage			Aluminum	Aluminum			Alloy Steel	Alloy Steel			PT02H-10-6P	PT02H-10-6P			Top	Top			0.48 in-lb/sec ²	0.48 in-lb/sec ²			7900 RPM	7900 RPM		<table border="0"> <tr> <td colspan="4" style="text-align: center;">PCB LOAD & TORQUE</td> </tr> <tr> <td colspan="4" style="text-align: center;">A PCB GROUP COMPANY</td> </tr> <tr> <td colspan="4"> PCB Load & Torque, Inc. 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: ltinfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com </td> </tr> </table>			PCB LOAD & TORQUE				A PCB GROUP COMPANY				PCB Load & Torque, Inc. 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: ltinfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com			
	5.3 lb	2.4 kg																																																										
	Keyed	Keyed																																																										
	Shaft	Shaft																																																										
	Strain	Strain																																																										
	Gage	Gage																																																										
	Aluminum	Aluminum																																																										
	Alloy Steel	Alloy Steel																																																										
	PT02H-10-6P	PT02H-10-6P																																																										
	Top	Top																																																										
	0.48 in-lb/sec ²	0.48 in-lb/sec ²																																																										
	7900 RPM	7900 RPM																																																										
PCB LOAD & TORQUE																																																												
A PCB GROUP COMPANY																																																												
PCB Load & Torque, Inc. 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: ltinfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com																																																												
<p><i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p> <p>ICP® is a registered trademark of PCB Group, Inc.</p>																																																												



Represented in India by

Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029