

Model Number 1631-04C	STRAIN GAGE LOAD CELL			Revision: E ECN #: 43825
Performance	ENGLISH	SI		OPTIONAL VERSIONS
Measurement Range	2000 lb	8896 N	[5]	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Sensitivity(± 10 %)	2 mV/V	2 mV/V	[6]	
Non-Linearity	≤ 0.05 % FS	≤ 0.05 % FS		
Hysteresis	≤ 0.03 % FS	≤ 0.03 % FS		
Non-Repeatability	≤ 0.02 %RO	≤ 0.02 %RO		
Resonant Frequency	2.4 kHz	2.4 kHz		
Creep(in 20 minutes)	≤ 0.08 %	≤ 0.08 %		
Environmental				
Overload Limit	3000 lb	13.3 kN		NOTES:
Load Limit(Side Force, F _x or F _y)	200 lb	890 N	[3]	[1]Nominal.
Load Limit(Bending Moment, M _x or M _y)	400 in-lb	45.2 Nm	[3]	[2]Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS.
Load Limit(Axial Torque, M _z)	400 in-lb	45.2 Nm	[3]	[3]Singularly applied, i.e. no other extraneous loads.
Temperature Range(Operating)	0 to +200 °F	-18 to +93 °C		[4]Over compensated operating temperature range.
Temperature Range(Compensated)	+70 to +170 °F	+21 to +77 °C		[5]FS - Full Scale.
Temperature Effect on Output(Maximum)	± 0.0008 %Reading/°F	± 0.0015 %Reading/°C	[4]	[6]RO - Rated Output.
Temperature Effect on Zero Balance(Maximum)	± 0.0015 %FS/°F	± 0.027 %FS/°C	[4]	[7]See Outline Drawing 46138 for Complete Dimensions
Electrical				
Bridge Resistance	350 Ohm	350 Ohm	[1]	
Excitation Voltage(Recommended)	10 VDC	10 VDC	[2]	
Insulation Resistance	>5x10 ⁹ Ohm	>5x10 ⁹ Ohm		
Zero Balance	± 1 % FS	± 1 % FS		
Output Polarity	+Tension	+Tension		
Physical				
Size (Length x Height x Width)	2.00 in x 3.0 in x 1.0 in	51.0 mm x 76.2 mm x 25.4 mm	[7]	
Weight	1.2 lb	544 g		
Mounting Thread	1/2-20 Thread	No Metric Equivalent		
Housing Material	Nickel Plated Steel	Nickel Plated Steel		
Sensing Element	Strain Gage	Strain Gage		
Deflection at Full Scale Capacity	0.003 in	0.05 mm		
Electrical Connector	10 ft - Integrated Cable	10 ft - Integrated Cable		
Electrical Connection Position	Side	Side		
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.				
				PCB Load & Torque, Inc. 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: ltinfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com



Represented in India by

Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029