


Model Number <b>377C20</b>	<b>PRECISION CONDENSER MICROPHONE</b>		Revision: A ECN #: 45005
<b>Performance</b> Nominal Microphone Diameter Frequency Response Characteristic Open Circuit Sensitivity Open Circuit Sensitivity(± 1.5 dB) Frequency Range(± 1 dB) Frequency Range(± 2 dB) Lower Limiting Frequency(-3 dB) Resonant Frequency(90° Phase Shift) Inherent Noise  Dynamic Range(3% Distortion Limit) Standards Designation(IEC 61094-4)	<b>ENGLISH</b> 1/2" Random Incidence 50 mV/Pa -26 dB re 1 V/Pa 5 to 6300 Hz 3.15 to 16,000 Hz 1.0 to 2.4 Hz 12,000 Hz 14 dB(A) re 20 μPa 146 dB re 20 μPa WS2D	<b>SI</b> 1/2" Random Incidence 50 mV/Pa -26 dB re 1 V/Pa 5 to 6300 Hz 3.15 to 16,000 Hz 1.0 to 2.4 Hz 12,000 Hz 14 dB(A) re 20 μPa 146 dB re 20 μPa WS2D	<b>OPTIONAL VERSIONS</b> Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
<b>Environmental</b> Temperature Range(Operating) Temperature Coefficient of Sensitivity(+14 to +122°F (-10 to +50°C)) Static Pressure Coefficient Humidity Coefficient of Sensitivity(0 to 100%, non-condensing) Influence of Axial Vibration(0.1g (1 m/s <sup>2</sup> ))	-40 to +248 °F 0.005 dB/°F -0.01 dB/kPa ± 0.001 dB/%RH 63 dB re 20 μPa	-40 to +120 °C 0.009 dB/°C -0.01 dB/kPa ± 0.001 dB/%RH 63 dB re 20 μPa	<b>NOTES:</b> [1] Typical. [2] Prepolarized [3] re 250 Hz
<b>Electrical</b> Capacitance(Polarized) Polarization Voltage	11 pF 0 V	11 pF 0 V	<b>SUPPLIED ACCESSORIES:</b> Model ACS-20 Calibration of Precision Condensator Microphones (1)  Entered: LK      Engineer: MT      Sales: MV      Approved: MT      Spec Number: Date: 10/13/2016    Date: 10/13/2016    Date: 10/13/2016    Date: 10/13/2016 <b>58702</b>   3425 Walden Avenue, Depew, NY 14043  <b>Phone: 716-684-0001</b> <b>Fax: 716-684-0987</b> <b>E-Mail: info@pcb.com</b>
<b>Physical</b> Housing Material Venting Mounting Thread(Preamplifier) Mounting Thread(Grid) Size (Diameter x Height)(with grid)  Size (Diameter x Height)(without grid)  Weight  <i>All specifications are at room temperature unless otherwise specified.  In the interest of constant product improvement, we reserve the right to change specifications without notice.</i> ICP® is a registered trademark of PCB Group, Inc.	Stainless Alloy Rear 0.4606 - 60 UNS 0.5 - 60 UNS 0.52 in x 0.64 in  0.5 in x 0.6 in  0.28 oz	Stainless Alloy Rear 11.7 mm - 60 UNS 12.7 mm - 60 UNS 13.2 mm x 16.2 mm  12.7 mm x 15.3 mm  7.8 gm	



Represented in India by  
**Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com**  
#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029